



This vacuum-ready, low vibration model produces an ultra-high quality finish and connects easily to central or portable vacuum systems. The 4152-HL extracts dust and particles through and around the pad keeping foreign matter away from the motor. The vacuum sanding pad features a unique design and large 13 mm (1/2") diameter holes for efficient operations. Virtually all dust is instantly channeled away from the work.

- ◆ 12 000 rpm, 0.15 kW (0.2 hp) motor for high performance finishing
- ◆ Vacuum-ready, connects easily to central or portable vacuum systems through a 360° swivel
- ◆ Low vibration operation delivers a smooth, swirl free finish
- ◆ Advanced composite rotor and vanes
- ◆ Non-lube, oil-free operation
- ◆ 360° swivel rear exhaust directs air away from operator
- ◆ Contoured composite housing is durable and comfortable
- ◆ Lightweight design, only 0.86 kg (1.89 lbs)

## Specifications at 6,2 bar (90 PSI)

<i>Part number</i>	<b>4152-HL</b>
<i>Ordering number</i>	<b>80134356</b>
<i>Pad size diameter</i>	<b>6 in / 152 mm</b>
<i>Orbit diameter</i>	<b>3/32 in / 2.5 mm</b>
<i>Type</i>	<b>Vacuum ready</b>
Also available with 152 mm pad & 5 mm orbit:	4151-HL
Also available with 75 mm pad & 2.5 mm orbit:	4152-HL-SR

### PERFORMANCE

<i>Rated power</i>	<b>0.2 hp / 0.15 kW</b>
<i>Free speed</i>	<b>12 000 rpm</b>

### AIR SYSTEM

<i>Air inlet (NPTF)</i>	<b>1/4 in</b>
<i>Min hose size</i>	<b>5/16 in / 8 mm</b>
<i>Average air consumption</i>	<b>8.0 cfm / 220 l/min</b>
<i>Air consumption at free speed</i>	<b>16.0 cfm / 448 l/min</b>
<i>Air consumption at load</i>	<b>15.5 cfm / 430 l/min</b>

### NOISE & VIBRATIONS

<i>Sound pressure</i>	<b>81.6 dB(A)</b>
<i>Vibration level</i>	<b>4.8 m/s<sup>2</sup></b>

### WEIGHT & DIMENSIONS

<i>Tool weight (without pad)</i>	<b>1.89 lbs / 0.86 kg</b>
<i>Shipping weight</i>	<b>3.01 lbs / 1.37 kg</b>
<i>Shipping dimensions (l x w x h)</i>	<b>205 x 165 x 115 mm</b>
<i>UPC/EAN Code</i>	<b>6 63023 01783 9</b>